



T A S M A N
LEATHER NORTH CAROLINA

ENCORE

TECHNICAL SPECIFICATIONS

RAW MATERIAL: USA STEERS & COWS

COLORS: SEQUOIA – DUNE – MINK – PEWTER – RED BROWN – BASIL – THUNDERCLOUD – LOAM – LOFT – GOLDENROD – GARNET – GREYSTONE – STINGRAY

| Product | Laboratory specs | | | | Inspection specs | |
|----------------------------|-----------------------|------------------|----------------------------|-------------------|------------------|--------------------------------|
| | Description | Method | Requirement | Units | Description | Requirement |
| E N C O R E | Tensile Strength | CIA 800 | 355 MIN | N/cm ² | Thickness | 1.1 +/- .01 mm |
| | Elongation at Break | CIA 800 | >40 | % | Brightness | 3 - 3.5 |
| | Slit Tear Stregth | ISO 3377-2 | MIN 30 | N | Color | According to the master sample |
| | Flexing | ASTM D 2097 | No cracks at 60 000 cycles | Flexing | | |
| | Crocking Dry | AATCC8 | Min 4 at 10 cycles | GS | | |
| | Crocking Wet | AATCC8 | Min 4 at 10 cycles | GS | | |
| | Finish Adhesion (Dry) | DIN EN ISO 11644 | MIN 3 | N/CM | | |